



MODEL - CAL50-6
6 Pin Connector
0...10,000 psig
4...20 mA

www.rhinotransducers.com
1-855-925-4520
MADE IN AMERICA

PRESSURE TRANSDUCERS FOR MEASUREMENT WHILE DRILLING



Compatible with ALL MWD Surface Systems, Rhino Pressure Transducers offer noise isolating technology to help your positive pulse measurement while drilling tool get to deeper depths with better decode, quality and telemetry confidence. With its rugged design, the Rhino Pressure Transducer will work on any WECO 1502 hammer union fitting.

FEATURES

RUGGED DESIGN

Built for the toughest Rig Site environments

NOISE ISOLATING TECHNOLOGY

Designed for AC Top Drive Rigs and Conventional Rotary Rigs

3 MONTH WARRANTY

Quick Repairs – Made in America

OPERATIONAL PARAMETERS

Pressure Ranges	0 - 10,000 psig
Amperage	4 - 20 mA
Voltage	8 – 30 V
Operating Temperature	-40C – 150C

Compatible with all MWD Surface Systems



MODEL - CAL50-6
6 Pin Connector
0...10,000 psig
4...20 mA

www.rhinotransducers.com
1-855-925-4520
MADE IN AMERICA

RHINO PRESSURE TRANSDUCER SPECIFICATIONS

PERFORMANCE

Accuracy	+/- 0.25% BFS LINEARITY
Thermal Error	< +/- 0.010 FSO/F Typical
Insulation Resistance	> 100 megohms
Frequency Response	1000Hz to 5K Hz
Temperature Operating	-40C to 150C

ELECTRICAL

Supply Voltage	8 VDC to 30 VDC
Output Signal	4 mA - 20 mA
Voltage	8 – 30 V
Circuit Protection	Reverse Polarity Protection
RFI/EMI Protection	Up to 2.9 GHz

SPECIFICATIONS

MODEL CAL50-6

Approvals	UL, CSA, GOST
RoHS-Conformity	Yes
CE-Conformity	
• Pressure Equipment Directive	97/23/EC
• EMC Directive	89/336/EEC emission (class B) and immunity according to EN 61 326
Shock Resistance	500g according to IEC 60068-2-27 (mechanical shock)
Vibration Resistance	10g according to IEC 60068-2-6 (vibration under resonance)
Wiring Protection	
Overvoltage protection	36VDC with 4... 20mA
Housing Material	Double wall stainless steel construction
Weight	10.0 lbs



MODEL - CAL50-6
6 Pin Connector
0...10,000 psig
4...20 mA

www.rhinotransducers.com
1-855-925-4520
MADE IN AMERICA

RHINO PRESSURE TRANSDUCER DIMENSIONS

